



Alpine (POU Water Cooler)

Our original square design cooler, the Alpine, now has a convenient and affordable POU Conversion Kit so that the cooler can be modified quickly and easily from a bottled cooler to a Point-of-Use cooler and back again, if necessary. Using our time-tested, non-solenoid double float system, with handy re-set button and easy to clean components, this new POU lid and esthetic cover make our standard cooler more versatile and responsive to today's market needs.

Alpine: Hot & Cold



POU cover



Touch Guard®
hot water faucet



Removable drip tray

ITEM		SPECIFICATIONS
Power rating		Single phase 220-240VAC 50Hz
Standard current	220-240VAC	Hot & Cold: 2.7A
Power Consumption	Cold	74W
	Hot	450W
Cold	Compressor	Single phase motor (TS24 LATG)
	Temp control	4-10°C (39.2-50°F)
	Refrigerant	R134a
	Capacity	3.2L (0.8 gal)
Hot	Heater	Band heater
	Temp control	Bimetal 74-92°C (165.2-197.6°F)
	Capacity (External Heater)	2L (0.5 gal)
	Capacity (Internal Heater)	1L (0.3 gal)
Refrigerant charge		25g (0.9 oz)
Product weight		Hot & Cold: 14.3kg (31.5 lb)
Product boxed weight		Hot & Cold: 16.3kg (35.9 lb)
Product dimensions		316(W X 319(D) X 980(H))mm
		12.4"(W)X 12.6"(D) X 38.6"(H)
Product boxed dimensions		330(W) X 340(D) X 1120(H))mm
		12.6"(W) X 13.4"(D) X 44.1 "(H)
Loading quantity		20' Container: 238 Units
		40' Container: 490 Units
IEC protection class		Class 1
Certifications		C-UL-US, CE, CB, CCC, SASO

This Company has a policy of continuous development and reserves the right to change specifications without notification. For further clarifications, please contact us at sales@crystalcoolers.com.