



Glacier (POU Water Cooler)

The Glacier Point-of-Use water dispenser is available in Hot & Cold models. The rounded cabinet and fluted front give the Glacier a classic Greek column design suitable for any environment. While being aesthetically pleasing, the polyethylene cabinet's smooth finish is easily cleaned and refurbished. This commercial grade cooler will deliver years of trouble free optimum performance.

Glacier: Hot & Cold



**Touch Guard®
hot water faucet**



Removable drip tray



**Hot water ON
and OFF switch**

Specifications:

ITEM		SPECIFICATIONS
Power rating		Single phase
		100V-115V 60Hz
Standard current		Hot & Cold: 6.2A
Power Consumption	Cold	74W
	Hot	450W
Cold	Compressor	Single phase motor (TS24 LATG)
	Refrigerant	R134a
	Temp range	4-10°C (39.2-50°F)
	Capacity	2.8L (0.7 gal)
Hot	Heater	Band heater
	Temp range	74-92°C (165.2-197.6°F)
	Temp control	82-89°C (179.6-192.2°F)
	Capacity (External Heater)	2L (0.5 gal)
	Capacity (Internal Heater)	1L (0.3 gal)
Refrigerant charge		25g (0.9 oz)
Product weight		Hot & Cold: 13.6kg (30.1 lb)
Product boxed weight		Hot & Cold: 15.5kg (34.2 lb)
Product dimensions		312(W) X 314 (D) X 980(H)mm
		12.2"(W) X 12.4"(D) X 38.6"(H)
Product boxed dimensions		330(W) X 340(D) X 1120(H)mm
		12.6"(W) X 13.4"(D) X 44.1 "(H)
Loading quantity		20' Container: 238 Units
		40' Container: 490 Units
IEC protection class		Class 1
Certifications		C-UL-US, CE, CB, CCC, SASO

This Company has a policy of continuous development and reserves the right to change specifications without notification. For further clarifications, please contact us at sales@crystalcoolers.com.